

SPARTAN SR4-BK Eclipse (Black Flash) camo + built-in viewer

Capture stunningly detailed pictures with the all-new SR4-BK Eclipse. With industry-leading IR LED Blackout (no glow) flash technology, you'll get vibrant photos / video clips during the day and clear, black and white photos / video clips at night. Never miss a thing with a 80-degree wide-angle lens and a 0.3 second trigger speed. On top of that, the front-facing 2" LCD screen of the Eclipse makes setup easier than ever by letting you check the camera's view and make adjustments accordingly.

FEATURES:

- Non cellular
- 110° wide angle lens
- Up to 24MP images and up to 1440P videos
- High quality colour photos and videos during the day
- Advanced blackout flash for monochrome photos and videos at night
- 2 inch front facing LCD screen for easy camera setup
- Built-in metal pitch-angle mount ensures the camera stays secure
- Cartridge-style battery compartment
- Store up to 512GB of photos and videos on a micro SD card

Model Number: **SR4-BK ECLIPSE**

Image Resolution: 5MP / 8MP / 24MP
Flash Type: Auto adjustable* night-time PHOTO / VIDEO illumination = Black flash (no glow)

* The auto-adjustable flash power feature minimizes over exposed images and video clips by automatically detecting the distance the target is from the camera during each trigger and adjusting the flash power / strength accordingly.

Flash Range: 30m+ Black flash (no glow)

Viewing screen: Built-in 2" IPS LCD (480x360mm) front-facing display
Video Resolution: 1440p (2560x1440) / 1080p (1920x1080) / 720p (1280 x 720) - with sound
Video Length: 5s / 10s / 15s / 30s
Trigger Speed: 0.3s
Trigger Intervals: 0s - 60min
Trigger Types: Motion (PIR) / Timer (Time Lapse) / Work Day

Time-lapse Intervals: Off / 5m / 10m / 30m / 1h / 4h / 12h / 24h
PIR Sensitivity: Adjustable (High / Normal / Low / Off)
PIR Type: Multi-zone
FOV (Field of View): 80° wide angle

Photo Burst Mode: 1-3 per trigger / activation

Photo+Video Mode: 1 Photo then 1 (10-30 second) video per single trigger

Memory: Micro-SD, up to 512Gb (sold separately)
Power source: 6 x AA (lithium, alkaline, or rechargeable 1.2v NiMH) - sold separately
External Power: Yes - compatible with 12v DC SLA battery / solar panel
Mounting: Built-in metal pitch-angle mount + Python lock hole / Tripod thread / Mounting strap
Padlock lockable: Yes (Latch and padlock loop)
Operation Temp: -20°C ~ 60°C
Operation Humidity: 5% - 90%
Weight: 350g
Dimensions: 24cm x 17cm x 9.3cm
IP Rating: IP65

