

CORE™ S-4K (119949C)

The CORE™ S-4K checks all the boxes one wants the most: The highest picture resolution with a 4K Single Sensor for best-in-class image & video quality, plus optimized battery life for maximum image captures and more time in the field without checking batteries. All in a compact design to stay hidden from eyes you don't want to alert – animal and human.

Bushnell is built around one simple principle to make sure our materials, components, and features give you the best images and information possible in every situation, every day. After all, why settle for "good" or "better" when you can have the best? That's Bushnell.

Recommendations:

- Batteries: Energizer Brand Lithium Batteries
- Memory Card: San Disk Brand SD Cards (up to 512GB Capacity)

- * Next Level with Best-In-Class 4K video
- * Up to 30MP Images
- * 4K Single Sensor
- * Pro image tuning
- * 1.5" colour View Screen
- * 40m Black LED Flash (No-Glow) Range
- * 3-Preset Menus + Advanced Mode
- * Dynamic Video
- * 0.2s trigger speed
- * 1 second Recovery Rate
- * 6 x AA batteries (not included)
- * Up to 12 Month Battery Life

TECHNICAL SPECIFICATIONS (119949C)

Lens:	FOV=50° Horizontal
Display Screen:	1.5" Colour viewing / programming screen
Image Size (pixel count in 16:9 format):	
• Low	2MP = 2048x1152
• Medium	4MP = 2592x1464
• High	23MP = 6400x3600
Image Size (pixel count in 4:3 format):	
• Low	2MP = 2048x1536
• Medium	5MP = 2592x1944
• High	30MP = 6400x4800
Video Sizes (with audio):	
- 4K	3840x2160 @ 30FPS
- 1080p	1920x1080 @ 60FPS
- 720p	1080x720 @ 30FPS
Video Length:	5-60 seconds.
PIR Sensitivity:	4 settings: Low/Normal/High/Auto
Operation:	User selectable: 24 Hour, Day only, or Night only (based on ambient light level)
Image stamp:	Date / Time / Temp / Moon
Response Time:	0.2 second (Photo), 0.7 second (Video). 0.5 second interval
Delay:	0.5s - 60s and 1m-60m programmable
Field Scan 2X:	Yes
Hybrid Capture:	Yes
Images per Trigger:	1—6 programmable
Illumination Mode:	Low, Fast Motion, Long Range (110' maximum range)
Power Supply:	6 x AA batteries, lithium (recommended) or alkaline
Stand-by Current:	> 0.8mW
Average Battery Life*:	Approx. 12 months @ 30 images per day average (15 day, 15 night w/LEDs)
Operating Temperature:	20 - 60°C (Storage temperature: -30 - 70°C)
Operating Humidity:	5% - 90%

